

# Teagle

# Topper 9

## Front & Rear Mounted Shaft Drive Topper



### Options

1000 rpm PTO (Factory Fitted)  
21 Spline PTO coupling

### SPECIFICATIONS

Cutting Width	2.75 m	9' - 0"
Overall Width	2.84 m	9' - 4"
Overall Length	1.99 m	6' - 6"
Cutting Height	12 mm - 100 mm	1/2" - 4"
Power Required	40 kW	55 HP
Linkage	Category 2	
Weight	500 kg	1,100 lb

Your local stockist:

The company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice.

- **Front and rear mounting** are standard features built into the machine.
- **Reversible PTO rotation** – just unbolt the centre gearbox and turn it through 180°.
- **540 or 1000 rpm gearbox ratios** are available – front mounting where the PTO runs at 1,000 rpm is not a problem.
- **Shaft drive** incorporating rubber couplings, between the gearboxes means that the rotors can be timed and overlapped to eliminate any possibility of uncut strips.
- **Spring steel swinging blades** mounted on spring steel blade holders reduce stone damage. The PTO shaft incorporates a shear bolt for added protection.
- **Good spread of cut material** is ensured by bolt on deflectors – easily reversed for front or rear mounting.



BLACKWATER, TRURO, CORNWALL TR4 8HQ

Tel 01872 560592 Fax 01872 561166

E-mail [sales@teagle.co.uk](mailto:sales@teagle.co.uk) Web [www.teagle.co.uk](http://www.teagle.co.uk)

# Teagle